

Keep upright at all times. Shake/stir well before and during application.

- **Barrettine Decking Oil has been specially formulated to offer Oil, Protection and Staining all in one application.**
- **It resists flaking and peeling and being water repellent helps prevent timber splitting and cracking.**
- **It can also be used on other wooden garden structures and is harmless to plants and pets when dry.**
- **Shake/stir well before and during application.**

WHERE TO USE

For use on all pre-treated, pressure treated and preservative impregnated timber, offers superb protection to Decking Boards, Deck Tiles and Balustrading. Also as a superior finish to sheds, Huts and Fencing.

Note: Cannot be used over timber that has been previously painted with conventional paints, varnishes, lacquers etc without first removing such barrier coatings.

COVERAGE

One coat - up to 8 sq metres per litre on smooth timber or up to 6 sp meters per litre on rough sawn timber.

PREPARATION

Decking has usually been pre-treated with a preservative. If using new, unpreserved timber treat with Barrettine Universal Preservative (ideally two coats). Leave to dry for 24 - 48 hours prior to using Decking Oil. Ensure all surfaces are clean, dry and free from dust, dirt and algae. Treat with Barrettine Knockout® Mould & Mildew Cleaner if necessary. New wood should be first wiped down with White Spirit to remove surface resins etc. Highly resinous timbers and some hardwoods may effect performance and final results - Test before use.

APPLICATION - SHAKE WELL

Decant into paint kettle and apply an even coat to all surfaces to ensure optimum performance. For best results, apply to all sides of decking before construction, brushing in the direction of wood grain. Normally one coat applied liberally with a wide bristle brush is sufficient, however should you require a deeper colour a second coat may be applied after 12-24 hours.

If desired Barrettine Decking Oil may be applied by synthetic roller or sprayer. However always back brush to ensure even coverage.

Leave for 24- 48 hours or until dry before subjecting to heavy foot traffic. Recoat as and when desired. Do not apply if the ambient temperature is below 5 Celsius, in damp conditions or rain is likely within 24 hours of application.

CLEANING

Remove as much of the product from brushes etc before cleaning with Barrettine White Spirit. Clean any spills before it is allowed to dry.

Note: Immediately after use saturate all soiled cloths with water and dispose of safely outside the home.

HEALTH AND SAFETY

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, Naphtha (Petroleum), Hydrotreated Heavy, Low Boiling Point Hydrogen treated Naphtha, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (contains less than 0,01 % w/w benzene)

HAZARD STATEMENTS

• Flammable liquid and vapour • May be fatal if swallowed and enters airways • May cause drowsiness or dizziness • Keep out of reach of children • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking • Keep container tightly closed • Avoid breathing fume, vapours, mist, spray • Use only outdoors or in a well-ventilated area • Wear eye protection, face protection, protective clothing, protective gloves • Dispose of contents/container in accordance with national regulations. • Contains 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate(55406-53-6). • May produce an allergic reaction • Repeated exposure may cause skin dryness or cracking

UN N° 1268



VERY HIGH: VOC content more than 50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (cat/A/f): 700 g/l (2007) 700 g/l (2010). This product contains max 568 g/l VOC

Barrettine Products Ltd.

St. Ivel Way, Warmley, Bristol BS30 8TY.

T: +44 (0) 0117 960 0060 F: +44 (0) 117 935 2437 E: sales@barrettine.co.uk www.barrettinePro.co.uk
Group Website: www.barrettine.co.uk