

PEEL HERE

Barrettine

TRUSTED BY THE PROFESSIONALS

PREMIER NOURISH & PROTECT
COLOURED WOOD PRESERVATIVE



TIMBER CUT END

PRESERVER

Long lasting end grain protection
from rot, fungi & blue stain

- ✓ Ideal for decking & other cut pressure treated timbers
- ✓ Deeply penetrates & protects the end grain

GREEN



UPF: 1010-00FK-R00G-NMCF



5 015861 005724

1 Litre e

R1

RISK MITIGATION MEASURES

This material and its container must be disposed of in a safe way. DO NOT CONTAMINATE FOOD STUFFS, EATING UTENSIL OR FOOD CONTACT SURFACES, WASH HANDS AND EXPOSED SKIN before meals and after use. KEEP IN A SAFE PLACE. UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY. AVOID ALL CONTACT WITH PLANT LIFE. COVER ALL STORAGE WATER TANKS before application. ALL BATS ARE PROTECTED UNDER THE WILDLIFE & COUNTRYSIDE ACT 1981. BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT NATURAL ENGLAND, SCOTTISH NATURAL HERITAGE OR THE COUNTRYSIDE COUNCIL FOR WALES. HAZARDOUS TO BEES. DO NOT USE ON BEEHIVES OR BEE KEEPING EQUIPMENT. 3-IODO-2-PROPYNYL-N-BUTYL CARBAMATE is carbamate compound which has weak anticholinesterase activity. DO NOT USE if under medical advise not to work with anticholinesterase compounds. FOR OUTDOOR USE. Also for use on windows/frames, external doors/frames (internal & external sections).

ADDITIONAL RISK MITIGATION MEASURES FOR USE BY PROFESSIONAL OPERATORS
Avoid excessive contamination of coveralls. The COSHH (Control of Substances Hazardous to Health) Regulations 2002 (as amended) apply to the use of this product at work. Refer to www.hse.gov.uk/pubns/guidance/sseries.htm
To avoid risk to man and the environment, comply with instructions for use.

ACTIVE INGREDIENT: 3-Iodo-2-propynyl butylcarbamate (IPBC) 0.624% w/w, Tebuconazole 0.284% w/w and Permethrin 0.06% w/w.
EXPIRY DATE: 2 years from production date. **OUT OF HOURS EMERGENCY TELEPHONE NO.** +44 (0) 1270 502891

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,
<2% aromatics, 3-iodoprop-2-ynyl butylcarbamate, tebuconazole, permethrin (ISO)



Danger

May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.
Contains 3-iodo-2-propynyl butyl carbamate and tebuconazole. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid release to the environment.
IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Store locked up
Dispose of contents and container in accordance with all local, regional, national and international regulations.
Use biocides safely. Always read the label and product information before use.

VERY HIGH VOC CONTENT >50% VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.

Peel back page to see full instructions for use inside.

St. Ivel Way, Warmley, Bristol. BS30 8TY
Tel: 0117 9600 060 Fax: 0117 9352 437
Email: sales@barrettine.co.uk www.barrettinePro.co.uk

PREMIER NOURISH & PROTECT COLOURED WOOD PRESERVATIVE is a low odour solvent borne ready to use product. Formulated to be used on pressure treated timber where it has been cut, drilled or worked in any way to expose the untreated inner wood. Protects against fungal decay such as wet rot, wood discolouring fungus and wood boring insect attack. Penetrates deeply into end grain wood providing a water repellent finish. Contains resins and oils to give a long lasting effect.

RANGE OF USE: For outside applications including joinery in external walls such as doors, windows and their frames (inner & outer surfaces), facades, carports, shutters, summer houses, gates and balcony railings. Also for use where wood is resting on the ground / hardstanding and only submitted to intermittent wetting (rain) such as garden furniture products. It is not suitable to treat wood for any in-ground use or where the wood is permanently subjected to continual wetting (streams, ponds etc). For a more comprehensive listing of suitable applications click 'Product Information' tab at www.barrettinePro.co.uk.

INSTRUCTIONS FOR USE: READ ALL PRECAUTIONS & THE FULL LABEL BEFORE USE

Apply the product liberally to the end grain and allow it to be absorbed. The ends of the timber can also be stood in Cut End Preserver for an hour to allow the product to deeply penetrate.

Application method: Amateur: BRUSH AND ROLLER.

Professional: BRUSH, DIP AND ROLLER.

Protect environment (e.g. Soil, plants, aquatic environment) from splashes of PNPC Preserver.

Amateur / Professional uses: Shake Well

Apply using a synthetic brush designed for solvent-borne products, spreading out thinly and evenly, ensure end grain is thoroughly treated along with cut and drilled areas. Reseal container after use. It is recommended that a minimum of 2 coats are applied depending on wood species and surface characteristics. Allow 6-12 hours drying time (touch dry) between coats. Application of successive coats will provide a darker finish and on smooth wood a higher sheen finish. If using the Clear Preserver in conjunction with a stain / wood dye it is recommended to apply the colourant before the Preserver, test effect on an off-cut initially.

Coverage: Effective against wood destroying fungi, blue stain and wood boring insects at 180 ml/m².

Drying time: 24 h under normal conditions (20°C/65% rel. humidity). Low temperatures, increased humidity and ingredients of some wood types may increase drying time.

FIRST AID MEASURES: AFTER SKIN CONTACT: Take off immediately all contaminated clothing, and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

AFTER CONTACT WITH EYES: Rinse immediately with plenty of water and seek medical advice if symptoms occur.

IF SWALLOWED: Rinse the mouth with water and give small amounts of water to drink (not in the case of loss of consciousness). Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms occur.

AFTER INHALATION: Move the exposed person into fresh air. Keep person warm and at rest. Provide artificial respiration by a trained person if breathing is irregular or arrested. It may be dangerous to the person providing aid by mouth-to-mouth resuscitation. Seek medical advice if symptoms are severe or long lasting. If unconscious, place in recovery position and get medical attention immediately.

IN GENERAL: Show this label if medical advice is needed.

PRECAUTIONARY INFORMATION: USE ONLY AS DESCRIBED ON THE LABEL.

The precautions generally recommended for handling wood protection products should be observed, e.g. Wearing of protective clothing, safety goggles and protective gloves (e.g. Nitrile rubber gloves). When using do not eat, drink or smoke. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. During application to in situ timbers and whilst surfaces are drying do not contaminate soil and surface waters with product. Do not empty into drains. Do not allow this product to reach aquatic environments, the ground or the sewer system. For Professional use, freshly treated timber must be stored after treatment under shelter or on impermeable hardstanding to prevent direct losses to soil or water and that any losses must be collected for reuse or disposal.

STORAGE: Store product in tightly closed original containers at temperatures above 0°C and below 30°C.

DISPOSAL INFORMATION: Completely empty cans can be recycled as normal.

Dispose left over product in the original container in compliance with local regulations. Do not dispose product residues or cleaning wastes into the sewer system (drains), into waterways or into the soil. Do not reuse empty containers.

European Waste Code (EWC)-Code

03 02 02: Organochlorinated wood preservative.

20 01 27: Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions : paint, inks, adhesives and resins containing dangerous substances.

**STATUTORY CONDITIONS OF APPROVAL RELATING TO USE
FOR USE ONLY AS A WOOD PRESERVATIVE**

FOR USE ONLY BY AMATEUR / PROFESSIONAL OPERATORS. READ ALL PRECAUTIONS BEFORE USE.

HSE No. 10007. PCS No. 98437

Users must comply in full with all their legal responsibilities under the control of Pesticides Regulations 1986 (as amended), including complying with all Conditions of Approval.

APPLICATION RATE: BRUSH/ROLLER AND SPRAYING: APPLY 180 ml OF PRODUCT PER SQUARE METER OF TIMBER SURFACE.

DIPPING: DIP TIMBER IN PRODUCT FOR AT LEAST 3 MINUTES.

Barrettine
TRUSTED BY THE PROFESSIONALS

J.V. Barrett & Co Ltd. Barrettine Products - St.Ivel Way, Warmley, Bristol. B530 8TY
Tel: 0117 9600 060 **Fax:** 0117 9352 437 **Email:** sales@barrettine.co.uk www.barrettinePro.co.uk
Group Website: www.barrettine.co.uk